

## Temperature Data Logger



---

## Specifications

**Alarm Type:** LED Indicator; Visual

**Ambient Operating RH Conditions :** 0-95% RH non-condensing

**Ambient Operating Temperature Conditions:** -10 to 176F (-23 to 80C)

**Battery Life (Avg):** 1 Year

**Cable Details:** USB - Male Series A plug to 5 pin Male Series B mini plug.

**Cable Length:** 6ft

**Calibration Options:** N100, N300, N400, N520

**Channels:** CH1: Temperature

**Data Capacity:** 32,000

**Delayed Start:** Yes

**Dimensions:** 0.9 x 2.1 x 3.1in

**Download Time:** 1 Minute

**Download Type:** USB

**IP Rating:** 20

**Included Accessories:** CR2450 Lithium Battery and Quick Start Guide. \*Software is not included.

**Minimum Software Version Required:** 10.0

**PC Requirements:** Microsoft Windows 98 or better; 16 MB RAM, 1 free USB root hub, CD drive, VGA monitor or better

**Power Source:** CR2450 Lithium Battery (User Replaceable)

**Power Status Indicator:** LED Indicator

**Sample Interval:** User Selectable (from 1 second to 24 hour intervals, in 1 second increments).

**Software Options:** A016, A026

**Temperature Accuracy:** +/-1.2F from -10 to 176F (+/-0.7C from -23 to 80C)

**Temperature Range:** -10 to 176F (-23 to 80C)

**Temperature Sensor Type:** Thermistor

**Unit Weight:** 1 lb

**Units/Pkg:** 1

**Warranty:** 12-Month Limited

## Calibrations

**N100** 1-Point NIST Traceable Calibration

**N300** 3-Point NIST Traceable Calibration

**N400** 3-Point Ultima NIST A2LA Accredited Calibration

---

## Accessories



**A016 - Software**

DicksonWare Software with USB Cable



**A026 - Secure Software**

DicksonWare Secure Software with USB Cable



**A061 - USB Download Cable**

USB Download Cable - length 6 feet (2m)



**N520 - Certificate of Validation**

Certificate of Validation



**A124 - CR2450 Battery**

3 Volt Lithium Coin Cell Battery

# Accessories



**A715 - Wall Mount Case**  
Small Locking Wall Mount Case